


Range of residential operators, extremely simple to install and completely safe to use thanks to full compliance with the current European standards.

Available with either 24V or 230V motors and either electromechanical or inductive limit switches.

Code	
R925227 00002	KIT DEIMOS FRA
R925243 00002	KIT DEIMOS 700 FRA
P925197 00001	DEIMOS
P925197 00003	DEIMOS PROX
P925196 00001	DEIMOS 700
P925200 00002	DEIMOS 800 F
R925227 00001	KIT DEIMOS ITA



## PLUS



Control unit with programming display and D-Track torque, speed and position management and control system in 24V versions. Incorporated dual channel radio receiver



Proximity limit switches for accurate, safe installations in any environmental conditions.



Backup battery power supply system, installable on-board unit (24V versions).

## Technical features

	DEIMOS	DEIMOS 700 DEIMOS 800 F
Control unit	ALPHA	
Power supply	230 V	230 V
Power input	270 W	290 W
Pinion module	4	4
Slowdown	no	no
Impact reaction	mechanical clutch	mechanical clutch
Locking	mechanical	mechanical
Release	knob with triangular key	knob with triangular key
Frequency of use	semi-intensive	semi-intensive
Environmental conditions	from -15 °C to 60 °C	
Actuator weight	11 kg	11 kg

## ACCESSORIES

	<b>ALPHA SD - D113680 00002</b> Universal control panel for a 230V/500W single phase operator		<b>B EBA BLUE ENTRY ANDROID 4 - P111531</b> BLUE-TOOTH expansion card for Blue Entry system. Manages up to 4 smartphones with the Android operating system
	<b>CP - D221073</b> Plastic rack, 4-module, cross-section 22 x 22 mm, length 1 m, screw-fitted into slots		<b>SFD - N999151</b> Base plate for DEIMOS series (supplied with operator)
	<b>BIR C - N190104</b> Rubber safety edge (H 30 mm), price per m		<b>STR - N190106</b> Pair of infrared sensors for DCW
	<b>VENTIMIGLIA NS - P111401 00001</b> Infrared device for BIR C or BAR C safety edges (conforms to EN 12978 Standard)		<b>RADIUS B LTA 230 R1 - D113748 00002</b> Flashing light with incorporated antenna for motors with power supply 230 V. Flashing beacon with built-in antenna for 230V motors
	<b>RADIUS B LTA 230 R2 - D113749 00002</b> Flashing light without incorporated antenna for motors with power supply 230 V. Flashing beacon without built-in antenna for 230V motors		<b>B 00 R02 - P123025</b> Wall mounting for B LTA series flashing beacons
	<b>Mitto B Rcb02 R1 - D111904</b> Transmitter with channels. Range . Power supply with 1 battery type 23 A		<b>Q.BO TOUCH - P121024</b> Wireless digital touch button panel 433Mhz rolling code.

## ACCESSORIES



**Q.BO KEY WM - P121022**  
Key selector for outdoor use with double contact.



**Q.BO KEY WM AV - P121023**  
Vandalproof key selector with metal structure. Vandalproof key selector with double contact, for outdoor use. Metal structure.



**DESME A15 - P111526**  
Pair of self-aligning photocells. Range 30 m. Power supply 24 V ac/dc. Pair of self-aligning photocells. Range 30 m. Power supply 24 V ac/dc.



**ERIS A30 - P111537**  
Pair of wireless photocells with the possibility of managing an active infrared or resistive sensitive edge. Pair of wireless photocells with possibility of management of an IR or resistive active safety edge. Possibility of directing the beam 180 ° horizontally and 20 ° vertically. Range 30 m. Power supply 24 V ac/dc.



**PHP - P903018**  
Pair of aluminium posts for THEA/DESME photocells



**SL BATI - P125033**  
SL BATI emergency battery kit for DEIMOS ULTRA BT



**CMS - D831081**  
Sign