P7 / P4,5

PAG-1	PAG-2	PAG-3	PAG-4

Product

Extremely sturdy and reliable hydraulic operators for industrial and condominium use. They can automate swing gate leaves up to 7m wide and weighing up to 500kg.

Smooth, silent gate movements are guaranteed by the extremely high-performance hydraulic system and the closing slowdown. Maximum precision in traction and thrust force control is guaranteed by the by-pass valve system.

Code		
P935061 00001	P4,5	Reversible hydraulic operator for swing gates up to 4.5 m. 500 kg in weight. Cycle time 28+slowdown sec. Useful travel 390 mm. max angle 123 $^{\circ}$.
P935061 00004	P4,5 WINTER	Reversible hydraulic operator for swing gates up to 4.5 m. 500 kg in weight. Cycle time 28+slowdown sec. Useful travel 390 mm. max angle 123 $^{\circ}$.
P935060 00001	P7	Reversible hydraulic operator for swing gates up to 7 m. 500 kg in weight. Cycle time 42+slowdown sec. Useful travel 390 mm. max angle 123 °.
P935060 00004	P7 WINTER	Reversible hydraulic operator for swing gates up to 7 m. 500 kg in weight. Cycle time 42+slowdown sec. Useful travel 390 mm. max angle 123 °.



PLUS



The rear articulated brackets and jointed rod make installation simple and reliable in all situations.



The brass release knob, protected with a personal key, facilitates the manual opening of the gate in the event of a power cut.



The closing slowdown guarantees silent, smooth movements on even the biggest gates. Also, the adjustment screw makes it possible to adapt the slowdown intensity to needs of each situation.

(800) 878-7829

www.BFTGateOpeners.com




RIGEL 5

Universal control panel for one or two 230V operators - 600+600W

RIGEL 5 D113693 00003

Application: universal control panel for one or two operators Board power supply: 230V single-phase

Operators power supply: 230V single-phase 600+600W



Main functions: automatic re-closing, separate motor working times, stays locked when closed, water hammer, 2/3/4 step logic, partial opening, fast closing, separate opening and closing

Compatibility: RIGEL 4



Technical features

	P4,5	P4,5 WINTER P7 WINTER	
Control unit	ALCOR N, RIGEL5		
Motor power supply	230 V	230 V	
Power input	250 W	250 W	
Maximum angle	123 °	123 °	
Slowdown	during closing	during closing	
Impact reaction	hydraulic clutch	hydraulic clutch	
Locking	solenoid lock	solenoid lock	
Frequency of use	very intensive	very intensive	
Release	reversible	reversible	
Environmental conditions	from -10 °C to 60 °C	from -30 °C to 60 °C	
Protection rating	IP55		

ACCESSORIES



ME - D111013

Control board for 12Vac solenoid lock for 23OV automation systems



ALPHA SD - D113680 00002

Universal control panel for a 230V/500W single phase operator



ALCOR N - D113706 00002

Control panel for one or two 230V/300W operators for swing gates



RADIUS B LTA 230 R1 - D113748

Flashing light with incorporated antenna for motors with power supply 230 V. Flashing beacon with built-in antenna for 230V motors



RADIUS B LTA 230 R2 - D113749 00002

Flashing light without incorporated antenna for motors with power supply 230 V. Flashing beacon without built-in antenna for 230V motors



ECB DX - D121016

Right-hand horizontal solenoid lock, 12-24V

www.BFTGateOpeners.com



ACCESSORIES



ECB SX - D121017

Left-hand horizontal solenoid lock, 12-24V



ECB VERTICALE - D121018

Vertical solenoid lock, 12-24V



CMS - D831081

Sign



EBP - P123001 00001

230Vac electric drop lock



EBPE 52 - P123006 00001

230Vac solenoid lock with zero stop resistance, also with release from outside for gates of max thickness 50 mm



EBPE 75 - P123008 00001

230Vac solenoid lock with zero stop resistance, also with release from outside for gates of max thickness 75 mm



EBP 24 - P123001 00013

24Vac solenoid lock, with 230/24V transformer installable in control panel



BIR C - N190104

Rubber safety edge (H 30 mm), price per



VENTIMIGLIA NS - P111401 00001

Infrared device for BIR C or BAR C safety edges (conforms to EN 12978 Standard)



NAT - N999131

Adapter for 230V hydraulic operators for inserting the spiral cable protection sheath



B 00 R02 - P123025

Wall mounting for B LTA series flashing beacons



Mitto B Rcb02 R1 - D111904

Transmitter with 2 channels. Range 50/100 m. Power supply 12 V with 1 battery type 23 A



Q.BO TOUCH - P121024

Wireless digital touch button panel 433Mhz rolling code.



Q.BO KEY WM - P121022

Key selector for outdoor use with double contact.



O.BO KEY WM AV - P121023

Vandalproof key selector with metal structure. Vandalproof key selector with double contact, for outdoor use. Metal structure.



DESME A15 - P111526

Pair of self-aligning photocells. Range 30 m. Power supply 24 V ac/dc. Pair of self-aligning photocells. Range 30 m. Power supply 24 V ac/dc.

(800) 878-7829

www.BFTGateOpeners.com



PAG-1	PAG-2	PAG-3	PAG-4

ACCESSORIES



PHP - P903018Pair of aluminium posts for THEA/DESME series photocells Height 522 mm

The contents of this catalogue (images, technical descriptions, illustrations) are the exclusive property of Bft s.p.a. Reproduction in any form and on any medium is forbidden. Copyright 2014. All rights reserved. The information given in this publication is only a guide. Bft reserves the right to make any changes without prior notice.

(800) 878-7829 www.BFTGateOpeners.com

