







# DESME

## DESME





Design, innovation and technology. These are the messages conveyed by the new range of photocells, which perfectly combine elegance, practicality, safety, ergonomics and functionality. The range includes adjustable and fixed photocells to cover every installation requirement.

### DESME 🖻 🛣 🛣

BFL

Code	Name		Description
P111527	DESME A15 O	new	Pair of photocells adjustable 40 ° horizontally and 10 ° vertically. IR signal synchronised to prevent any risk of blinding. Range 30 m. Power supply 24 V ac/dc.
P111526	DESME A15	new	Pair of self-aligning photocells. Range 30 m. Power supply 24 V ac/dc. Pair of self-aligning photocells. Range 30 m. Power supply 24 V ac/dc.









· DISCOVER U-LINK

· Product

	DESME A15 O	DESME A15
Voltage	24	۴V
Horiz. adjustment	40 °	
Vert. adjustment	10 °	
Range	30	lm
Protection rating	IP	55



www.BFTGateOpeners.com





Product

CHNICAL FEATURES

### ACCESSORIES

· DISCOVER U-LINK

	Code	Name		Description
	P903018	РНР	new	Pair of aluminium posts for THEA/DESME series photocells Height 522 mm
	P903019	PHP2	new	Pair of double aluminium posts for THEA/DESME series photocells. Height 1038 mm
U	P903021	PHP ADA CC	new	Pair of adapters for the installation of THEA/DESME photocells on CC posts
[]]	P903022	PHP BI	new	Dual-face adapter for THEA/DESME photocells
	P903023	PHP BA1		Support for mounting THEA/DESME photocells on Giotto, Moovi and Michelangelo enclosures
-5	P903024	ACV20	new	Vandal-proof protection for DESME photocells
<b>P</b> .	P903020	APL	new	Pair of foundation plates for PHP posts



www.BFTGateOpeners.com







Product

CHNICAL FEATURES

CCESSORIES

· DISCOVER U-LINK

# What is U-Link?

The innovative technology that gives you new power

An exclusive Bft innovation: U-Link (Universal Link) is an exclusive Bft platform that allows the creation of technological ecosystems. In Home Automation Access, it allows communication with all the home access automation devices of any brand. So you save time and can control everything with ease, without any worries.

It is intuitive Easy to install and use

It is scalable Allows an unlimited number of devices to be added

It is flexible Allows the creation of groups of interconnected products

It is practical Works with or without a web connection

It is functional Parameters can be controlled remotely via dedicated applications





BEL

### DISCOVER U-LINK

### All in one scheme: discover this amazing technology

A unique platform allowing the creation of technological ecosystems offering a wide range of solutions for different sectors.

Thanks to the B-Eba cards and the Clonix U-Link receiver, this proprietary platform featured by Bft products adapts to any protocol and access automation product (even BFT, non-native U-Link or non-BFT products), and is used in various sectors. Each device thus becomes smart and can be interconnected with other systems, thanks to a language that becomes universal.

### U-Base 2

Software to install and easily and comfortably carry out maintenance and identify any malfunction of U-link compatible operators.



### U-SDK

U-Sdk is the innovative application that can make Bft automation systems compatible and easily integrated with a BMS network for the supervision of buildings.



SECTORS

An innovative and easy to install system for easily managing all home automation



### U-Control

U-Control is the application that helps the quick and easy integration of BFT automation systems in large building management systems.

attentive to daily needs: thanks to the use of U-link the house gate can now be opened with just your smartphone.





### Clonix U-Link Allows the connection of non-native U-Link

products or non-Bft products to U-Link systems.

Bft operators, non-native U-Link products or a product belonging to other brands: can they be connected to U-Link? Yes, thanks to the Clonix receivers. Accessories that know no limits.



#### B-eba A direct line with your operators.

B-eba expansion cards allow the connection of external devices, such as PCs, smartphones and tablets, to a Bft operator or Clonix receiver, or the connection of several Bft products in a U-Link network. These accessories integrate with U-Link technology and Bluetooth, Z-Wave, TCP/IP protocols, as well as the RS485 serial connection. A device that fully translates what Bft V means for interconnectivity.

### www.BFTGateOpeners.com